

KVM over IP transmitter

KF6900T

- RS-232 support
- USB, DVI-I console
- Up to 1920 x 1200 @60Hz
- · Virtual media, microphone, speakers
- Advanced security and user settings



Dual display KVM over IP transmitter KF6940T

- RS-232 support
- Up to 1920 x 1200 @60Hz
- USB, DVI-I console, dual display
- Virtual media, microphone, speakers
- Advanced security and user settings



KVM over IP receiver

KE6900R

- RS-232 support
- USB, DVI-I console
- Up to 1920 x 1200 @60Hz
- · Virtual media, microphone, speakers
- Advanced security and user settings



Dual display KVM over IP receiver KE6940R

- RS-232 support
- Up to 1920 x 1200 @60Hz
- USB, DVI-I console, dual display
- Virtual media, microphone, speakers
- Advanced security and user settings



Optional **Matrix Manager software** for flexible connectivity CCKM

- · Centralized management
- Advanced security and user settings
- · Multipoint-to-multipoint connectivity
- Videowall capability up to 8 by 8 displays






Control room, oil platform, Italy

An Italian SI specialized in processautomation of industrial plants, with a focus on DCS, SCADA/HDMI, PLC, needed several computers to be safely stored in a server room, while still be accessible from 5 different control rooms.

reseller, both active in the IT market and control room business, the ATEN team installed several KVM over IF extenders.



Do you have a similar installation or project?

Contact sales@aten.be, our pre-sales team would be glad to assist you.