

## VC925 / VC985 操作說明

**VC925: DisplayPort 轉 VGA 轉接器**

**VC985: DisplayPort 轉 HDMI 轉接器**

VC925



VC985



### 操作說明

1. 將 VC925 / VC985 上的 DisplayPort 接頭連接到 DisplayPort 來源裝置
2. (a) 再用一條 VGA 線材將 VC925 連接至 VGA 顯示裝置  
(b) 再用一條 HDMI 線材將 VC985 連接至 HDMI 顯示裝置

BSMI

D33866  
RoHS

設備名稱: DisplayPort 轉 VGA 轉接器/ DisplayPort 轉 HDMI 轉接器 Equipment name				型號 (型式) : VC925/VC985 Type designation (Type)		
單元 Unit	限用物質及其化學符號 Restricted substances and its chemical symbols					
	鉛Lead (Pb)	汞Mercury (Hg)	鎘Cadmium (Cd)	六價鉻 Hexavalent chromium (Cr <sup>+6</sup> )	多溴聯苯 Polybrominated biphenyls (PBB)	多溴二苯醚 Polybrominated diphenyl ethers (PBDE)
電纜線 Cable	—	○	○	○	○	○
印刷電路部 件 PCBA	—	○	○	○	○	○
塑膠/其他 部件 Plastic /Others parts	○	○	○	○	○	○
金屬部件 Metal parts	—	○	○	○	○	○
<p>備考1. “超出0.1 wt %” 及 “超出0.01 wt %” 係指限用物質之百分比含量超出百分比含量基準值。 Note 1 : “Exceeding 0.1 wt %” and “exceeding 0.01 wt %” indicate that the percentage content of the restricted substance exceeds the reference percentage value of presence condition.</p> <p>備考2. “○” 係指該項限用物質之百分比含量未超出百分比含量基準值。 Note 2 : “○” indicates that the percentage content of the restricted substance does not exceed the percentage of reference value of presence.</p> <p>備考3. “—” 係指該項限用物質為排除項目。 Note 3 : The “—” indicates that the restricted substance corresponds to the exemption.</p>						

代理商：宏正自動科技股份有限公司

地址：新北市汐止區大同路二段 125 號三樓

- 最大額定電壓: 3.3Vdc, 0.5A

- 最大操作環境溫度: 50°C