

2M / 3M / 5M / 10M / 15M / 20M / 30M VGA Cable

2L-2502/2L-2503/2L-2505/2L-2510/2L-2515/2L-2520/2L-2530

- The VGA Cable is designed to provide a high quality VGA connection, ideally suited for high resolution applications up to 1920 x 1200. This durably constructed VGA video cable eliminates the picture ghosting and fuzzy images, guaranteeing users the ultimate AV experiences.



Features

- Optimized for analog signal transmission
- VGA cable with 15-pin male input and output
- Bend Radius: 60°*
- Outer shielded material: Al Mylar tape
- A range of cable lengths, available from 2 to 30 m
- Flame Test UL 758, CSA C22.2 No.210 compliant
- Compatible with ATEN VGA products

Note:* Swings 3000 times between angles of +/- 60 degrees, at a frequency of 40 times per minute

Specifications

Function	2L-2502	2L-2503	2L-2505	2L-2510	2L-2515	2L-2520	2L-2530
Conductor							
Material	Tinned Copper						
Conductor Diameter	30 AWG						
Jacketed							
Material	Jacket: PVC Shielding: AL-Mylar						
Connectors							
Video	HDB-15 Male HDB-15 Male						
Cable Length	2 m	3 m	5 m	10 m	15 m	20 m	30 m

Product information is subject to change without prior notice.

ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
 www.aten.com E-mail: marketing@aten.com

Publish Date: 12/2017 V1.0



© Copyright 2017 ATEN® International Co., Ltd.
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
 All rights reserved. All other trademarks are the property of their respective owners.