

master view™ max

Slideaway LCD KVM Switch



Diagram



8 or 16 PCs

Model: **CL1208**
CL1216

Features

- Integrated KVM console featuring a 15" or 17" LCD monitor in 1U high rack mountable Slideaway housing
- Slideaway™ housing is specifically designed with clearance - top and bottom - for smooth operation in a 1U high system rack
- Dual consoles
- Improved design-Single person installation (Optional)
- Daisy chain up to 31 additional CS-1216A units and control up to 512 computers
- Less than 1U high mountable rack
- Port selection via Pushbutton, Hotkey and OSD
- Two level password security - only authorized user view and control the computers - up to four users plus an administrator with separate profiles for each
- DDC emulation of the LCD monitor - VGA settings of every connected computer are automatically adjusted for optimal output to the LCD monitor

Specifications

| Function | | CL1208 | CL1216 |
|---------------------|-----------------------|------------------------------------|-----------------------------------|
| Computer | Direct | 8 | 16 |
| Connections | Max. | 256 (via Daisy Chain) | 512 (via Daisy Chain) |
| Port Selection | | Pushbutton, Hotkey, OSD | |
| Connectors | Second Console | 1 x 6-pin Mini-DIN Female (Purple) | 1 x HDB-15 Female (Blue) |
| | Ports | 1 x 6-pin Mini-DIN Female (Green) | 1 x 6-pin Mini-DIN Female (Green) |
| | KVM Ports | 8 x SPHD-15 Female (Yellow) | 16 x SPHD-15 Female (Yellow) |
| | Chain Port | 1 x DB-25 Male (Black) | 1 x DB-25 Male (Black) |
| | F/W Upgrade | 1 x RJ-11 Female (Black) | 1 x RJ-11 Female (Black) |
| | Power | 1 x 3-prong AC Socket | 1 x 3-prong AC Socket |
| Switches | F/W Upgrade | 1 x Slide | 1 x Slide |
| | LCM Adjustment | 4 x Pushbutton | 4 x Pushbutton |
| | Port | 8 x Pushbutton | 16 x Pushbutton |
| | KM Reset | 1 x Semi-recessed Pushbutton | 1 x Semi-recessed Pushbutton |
| LEDs | Power | 1 x Rocker | 1 x Rocker |
| | On Line | 8 (Orange) | 16 (Orange) |
| | Selected | 8 (Green) | 16 (Green) |
| | Num Lock | 1 (Blue) | 1 (Blue) |
| | Caps Lock | 1 (Green) | 1 (Green) |
| Emulation | Keyboard/ Mouse | PS/2 | PS/2 |
| | 15" LCD | 1024 x 768; DDC2B | 1024 x 768; DDC2B |
| Video | 17" LCD | 1280 x 1024; DDC2B | 1280 x 1024; DDC2B |
| | Scan Interval | 1-255 Seconds | 1-255 Seconds |
| I/P Rating | | 100-240V AC; 50/60 Hz; 1A | |
| Power Consumption | 15" LCD | 120V, 21W/230V, 23W | 120V, 22W/230V, 26W |
| | 17" LCD | 120V, 23W/230V, 25W | 120V, 26W/230V, 28W |
| Environment | Operating Temp | 0-40°C | |
| | Storage Temp | -20-60°C | |
| | Humidity | 0-80% RH, Non-condensing | |
| Physical Properties | Housing | 15" LCD | 14.10 kg |
| | | 17" LCD | 14.30 kg |
| | Dimensions(D x W x H) | | 62.60 x 48.00 x 4.20cm |

| Rack Mounting Kit | Depth |
|-------------------|--------------|
| Long (Optional) | 68cm - 110cm |
| Short (Standard) | 42cm - 82cm |

| Easy Installation Rack Mounting Kit | Depth |
|-------------------------------------|--------------|
| Long (Optional) | 68cm - 105cm |
| Short (Optional) | 52cm - 70cm |