CS1762a/CS1764a



USB DVI KVMP™ Switch

The CubiQ™ CS1762a/CS1764a USB DVI KVMP™ Switch charts a revolutionary new direction in KVM (Keyboard, Video, Mouse) switch functionality by combining a 2/4 port KVM switch with a 2 port USB 2.0 hub at the same time as it provides an interface for a digital monitor (DVI). In addition, the CS1762A/CS1764A comes with ATEN's new Video DynaSync™ technology, which optimizes display resolution, and power on detection, which means if one computer is powered off, the CS1762A/CS1764A will automatically switch to the next powered-on computer.

As a KVM switch, it allows users to access two or four computers from a single USB keyboard, USB mouse, and monitor console. As a USB 2.0 hub, it permits each computer to access any peripherals connected to the hub on a 'one computer at a time' basis.






















- One USB console controls two (CS1762A) or four (CS1764A) DVI computers and two additional USB 2.0 devices
- · 2-port USB 2.0 hub built in
- Fully compliant with the USB 2.0 specification
- Computer selection via front panel pushbuttons, hotkeys, and mouse
- Audio enabled full bass response provides a rich experience for 2.1 channel surround sound systems
- Multiplatform support Windows, Linux, Mac, and Sun
- Supports widescreen resolutions
- Superior video quality 1920 x 1200
- Independent switching of KVM, USB, and Audio focus
- DVI digital and analog monitor support fully compliant with the DVI specifications
- · HDCP compatible
- Video DynaSync™ exclusive ATEN technology optimizes display resolution and eliminates boot-up display problems
- Power on detection if one computer is powered off, the switch will automatically switch to the next powered-on computer
- Console mouse port emulation/bypass feature supports most mouse drivers and multifunction mice
- · Complete keyboard emulation for error-free booting
- · Mac/Sun keyboard support and emulation*
- Multilingual keyboard mapping supports English, Japanese, and French kevboards
- · Auto Scan Mode for monitoring all computers
- · Firmware upgradable
- * 1.PC keyboard combinations emulate Mac/Sun keyboards 2. Mac/Sun keyboards only work with their own computers

Setup



Specifications -----

Function			CS1762A	CS1764A
Computer Connections			2	4
Port Selection			Front Panel Pushbuttons; Hotkey, Mouse	
Connectors	Console Ports	Keyboard	1 x USB Type A Female (White; front panel)	1 x USB Type A Female (Black; rear panel)
		Video	1 x DVI-I Female (White)	
		Mouse	1 x USB Type A Female (white; front panel)	1 x USB Type A Female (Black; rear panel)
		Speakers	1 x Mini Stereo Jack Female (Green; rear panel)	2 x Mini Stereo Jack Female (Green; 1 x fror panel, 1 x rear panel)
		Mic.	1 x Mini Stereo Jack Female (Pink; rear panel)	2 x Mini Stereo Jack Female (Pink; 1 x front panel, 1 x rear panel)
	KVM Ports	Keyboard/ Mouse	2 x USB Type B Female (White)	4 x USB Type B Female (White)
		Video	2 x DVI-I Female (White)	4 x DVI-I Female (White
		Speakers	2 x Mini Stereo Jack Female (Green)	4 x Mini Stereo Jack Female (Green)
		Mic.	2 x Mini Stereo Jack Female (Pink)	4 x Mini Stereo Jack Female (Pink)
	Power		1 x DC Jack	1 x DC Jack
	USB Hub		2 x USB Type A Female (Black, rear panel)	2 x USB Type A Female (White; 1 x front panel, x rear panel)
Switches	Selected		2 x Pushbutton	4 x Pushbutton
LEDs	On Line / Selected		2 (Orange)	4 (Orange)
	USB Link		2 (Green)	4 (Green)
Emulation	Keyboard / Mouse		USB	
Video			1920 x 1200	
Scan Interval			1–99 secs. (5 secs. default)	
Power Consumption			DC 5.3V, 9.0 W	DC 5.3V, 10.7 W
Environment	Operating Temp.		0-50°C	
	Storage Temp.		-20-60°C	
	Humidity		0–80% RH, Non-condensing	
Physical Properties	Housing		Metal	
	Weight		0.73 kg	0.94 kg
	Dimensions(L x W x H)		21.00 x 8.70 x 5.50 cm	27.00 x 8.70 x 5.50 cm

