



## CS64A

**Features** 

computers

DDC2B

operationNon-powered

• All-in-one design

• With speaker support

4-Port PS/2 KVM Switch

 CS64A KVM Switch has a handy design integrating with 6 feet of cables.
It can control 4 servers via a single console.





• Compact design, built-in 1.8 m (6 feet) cables

• Superior video quality – up to 2048 x 1536;

• Auto Scan function to monitor computer

• One PS/2 console controls four PS/2

## Console Nonitor Speakers Keyboard CS64A CS64A

## Specification )

Function			CS64A
Computer Connections			4
Port Selection			Hotkeys
Connectors		Keyboard	1 x 6-pin Mini-DIN Female (Purple)
	Console	Video	1 x HDB-15 Female (Blue)
	Ports	Mouse	1 x 6-pin Mini-DIN Female (Green)
		Speaker	1 x Mini Stereo Jack Female (Green)
	KVM Ports	Keyboard	4 x 6-pin Mini-DIN Male (Purple)
		Video	4 x HDB-15 Male (Blue)
		Mouse	4 x 6-pin Mini-DIN Male (Green)
		Speaker	4 x Mini Stereo Plug Male (Green)
LEDs	Selected		4 x Green
Cable Length	Computers		1.8m
Emulation	Keyboard/Mouse		PS/2
Video Resolution			2048 x 1536; DDC2B
Scan Interval			5 Seconds
Environment	Operating Temp		0-50°C
	Storage Temp		-20-60°C
	Humidity		0-80% RH Non-condensing
Physical Properties	Housing		Plastic
	Weight		0.83 kg
	Dimensions (L x W x H)		7.86 x 7.86 x 3.06 cm

\* The specifications and pictures are subject to change without notice.

## ATEN International Co., Ltd. 3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan Phone: 886-2-8692-6789 Fax: 886-2-8692-6767 www.aten.com E-mail: marketing@aten.com

